

Everest SprayClean systems are designed to clean the parts, automatically with pressurized hot water and bio-degradable detergents. SprayClean systems are front loading machines. SprayClean models have heating insulation for the tank, vapour extraction, pneumatic lid as standart equipments. Also rinsing and drying processes could be added in this models according to customer requirments. MultiStage systems are controlled with PLC system. Optional equipments are disc type oil skimmers, oil water separator units, filtration units, discharge pumps, loading car, washing cabin insulationetc



TECHNICAL FEATURES

| MODEL | | PROCESS | BASKET DIAMETER | LOADING WEIGHT | LOADING HEIGHT | EXTERNAL DIMENSIONS | | | | TANK CAPACITIES | PUMP RATE | PUMP PRESSURE | HEATING |
|-------------------|--------------------|------------------------------|--------------------|-------------------|-------------------|---------------------|--------|------------------------|----------------------|--------------------|--------------|------------------|------------|
| | | | | | | WIDTH | LENGTH | HEIGHT (LID CLOSED) | HEIGHT (LID OPEN) | | | | |
| | | | mm | kg | mm | mm | mm | mm | mm | lt | lt/min | bar | kW |
| SPRAYCLEAN W | SprayClean 90-W | Washing | 900 | 300 | 500 | 1400 | 1550 | 2050 | 2700 | 250 | 140 | 3 | 7,5 |
| | SprayClean 120-W | | 1200 | 450 | 650 | 1750 | 1950 | 2150 | 2900 | 400 | 190 | 3,2 | 15 |
| | SprayClean 150-W | | 1500 | 600 | 750 | 2100 | 2400 | 2400 | 3400 | 550 | 250 | 3,3 | 22,5 |
| | SprayClean 180-W | | 1800 | 800 | 900 | 2400 | 2700 | 2600 | 3800 | 700 | 320 | 4 | 22,5 |
| SPRAYCLEAN WR | SprayClean 90-WR | Washing Rinsing | 900 | 300 | 500 | 1900 | 1550 | 2050 | 2700 | 250/180 | 140/120 | 3 / 2 | 7,5/7,5 |
| | SprayClean 120-WR | | 1200 | 450 | 650 | 2250 | 1950 | 2150 | 2900 | 400/250 | 190/140 | 3,2 / 3 | 15/7,5 |
| | SprayClean 150-WR | | 1500 | 600 | 750 | 2100 | 3000 | 2400 | 3400 | 550/360 | 250/190 | 3,3 / 3,2 | 22,5/ 15 |
| | SprayClean 180-WR | | 1800 | 800 | 900 | 2400 | 3300 | 2600 | 3800 | 700/450 | 320/250 | 4 / 3,3 | 22,5/15 |
| SPRAYCLEAN WRD | SprayClean 90-WRD | Washing Rinsing Drying | 900 | 300 | 500 | 1900 | 1550 | 2200 | 2700 | 250/180 | 140/120 | 3 / 2 | 7,5/7,5/9 |
| | SprayClean 120-WRD | | 1200 | 450 | 650 | 2250 | 1950 | 2300 | 2900 | 400/250 | 190/140 | 3,2 / 3 | 15/7,5/12 |
| | SprayClean 150-WRD | | 1500 | 600 | 750 | 2100 | 3000 | 2600 | 3400 | 550/360 | 250/190 | 3,3 / 3,2 | 22,5/15/18 |
| | SprayClean 180-WRD | | 1800 | 800 | 900 | 2400 | 3300 | 2800 | 3800 | 700/450 | 320/250 | 4 / 3,3 | 22,5/15/24 |

***Dimensions are for reference purposes only, external dimensions can change according to selected options

Everest Elektromekanik Makine ve Sistemleri Sanayi ve Tic. Ltd. Şti.

I.O.S.B Bağcılar Güngören Sanayi Sitesi Metro AVM A-Blok No:9 İkitelli-Başakşehir-İstanbul / TURKEY

Tel: (+90) 212 671 25 85 - Fax: (+90) 212 671 25 89 - E-mail: info@everestultrasonic.com - Web:www.everestmakine.com