

Small and fine - the anniversary machine MAFAC PURA



Benefits for the user

- Patented rotating multi-side spray system with counter-rotating basket receptacle system.
- Compact design with minimum space requirement.
- Large-capacity holding tank to ensure long useful life of the process water.
- Removable basket filters for collecting coarse dirt particles in the return flow.
- Powerful optional coalescence oil separator system with high-level monitoring of the oil collection tank.
- Steam extraction with mist collector, return of condensation and condensate.
- Hinged door as functional loading and unloading platform.
- Simple and convenient operation via the integrated Siemens LOGO! text display.
- Ultra-fine filtration in the main flow for removing small dirt particles before cleaning.
- The hot air pulse blowing system keeps residual water to a minimum for a higher degree of dryness of the parts.
- Cleaning chamber with viewing window for monitoring the cleaning process.
- Plug and Play: Available at short notice and immediately ready for use.
- Voltage range designed for worldwide use.

Standard features:

- Innovative machine design for quick maintenance and easy servicing
- Front loading with hinged door and sliding plate
- Rotating spray system with counter-rotating basket receptacle system
- Standard Euro baskets can be used (471x321x200 mm or 521x321x200 mm)
- Stationary hot air pulse blowing system
- Basket filter in return flow
- Water heating system with analogue temperature control and cut-off
- Steam extraction with condensation and mist separator
- Large tank with a capacity of 320 litres
- Levelling set

Options:

- Coalescing oil separator with high-level monitoring of the oil collection tank (45 l)

Accessories:

- Initial equipment with cleaning agent and basket
- Collection basin acc. to German Water Resources Act
- Drip pan

Cleaning process tank 1:

Spraying pressure pump standard version			Return filtration		Pre-run filtration	
Flow volume	Pressure	Output	Grade	Surface area	Grade	Surface area
380-460 V / 50 Hz approx. 100 l/min	380-460 V / 50 Hz approx. 2,5 bar	2,2 kW	150 µm	0,197 m²	100 µm	0,16 m²
380-460 V / 60 Hz approx. 130 l/min	380-460 V / 60 Hz approx. 4 bar					

Tank 1:	Contents	Heating time	Temperature	Heating capacity
	320 l	ca. 1 h	max. 75°C	380-460 V / 50 Hz approx. 10,0 kW 380-460 V / 60 Hz approx. 12 kW

Connections:	Electrical	V Ph Hz kVA	380-460 V 3~/PE 50 Hz approx. 14 kVA 380-460 V 3~/PE 60 Hz approx. 16 kVA
	Compressed air	inch bar	Rp ¾ 5...8
	Fresh water	inch bar	Rp ¾ 0,5...10
	Waste water	inch	Rp 1½
	Exhaust air	mm	113 x 105

Extraction/condensation:	Mean volumetric flow rate	600 m³/h
--------------------------	---------------------------	----------

Drying system:	Flow volume	Pressure	Temperature
Pulse blowing system	~3300-3400 l/min	3-5 bar	< 45°C

Dimensions:	Depth (mm)	Width (mm)	Height (mm)
Usable space max.	471/521	321	200
Outside dimensions	1250	950	1600
Loading height (with levelling set)			850-870

Weight:	Batch		max. 50 kg		
	Machine	without liquid	430 kg		
		with liquid	750 kg		
		with liquid and oil separator	795 kg		

Machine colour:	Light grey	Light green
	RAL 7035	similar to RAL 6027



Parts Cleaning. Systems and Solutions.

MAFAC - E. Schwarz GmbH & Co. KG
Max-Eyth-Straße 2, D-72275 Alpirsbach
Tel. + 49(0)7444 9509-0, Fax 950999
E-Mail: info@mafac.de, www.mafac.de